

# Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 26.01.2009

Revision: 26.01.2009

## 1 Identification of the substance/preparation and of the company/undertaking

· **Product details**

- **Trade name:** *teslanol Lectro Clean "SP" 400 ml / 200 ml*
- **Application of the substance / the preparation** *Solvent Cleaner*

· **Manufacturer/Supplier:**

wentronic - Electronic Components Handels GmbH  
 Pillmannstrasse 12  
 D-38112 Braunschweig  
 Deutschland / Germany  
 Telefon +49-(0)531-210 58-0  
 Telefax +49-(0)531-210 58-22  
 office@wentronic.com

· **Further information obtainable from:**

Vertrieb / Sales Department (über Zentrale / via switchboard)  
 Telefon +49-(0)531-210 58-0  
 Telefax +49-(0)531-210 58-22  
 office@wentronic.com

· **Information in case of emergency:**

Telefon +49-(0)531-210 58-0  
 Telefax +49-(0)531-210 58-22  
 office@wentronic.com

## 2 Hazards identification

· **Hazard description:**



*Xi Irritant*

*F+ Extremely flammable*

*N Dangerous for the environment*

· **Information concerning particular hazards for human and environment:**

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

Warning! Pressurized container.

Has a narcotizing effect.

R 12 Extremely flammable.

R 38 Irritating to skin.

R 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R 67 Vapours may cause drowsiness and dizziness.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking.

Without sufficient ventilation formation of explosive mixtures may be possible.

Keep out of the reach of children

· **Classification system:**

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

## 3 Composition/information on ingredients

· **Chemical characterization**

- **Description:** *Mixture: consisting of the following components.*

· **Dangerous components:**

CAS: 64742-49-0

Naphtha (petroleum), hydrotreated light

25-50%

EINECS: 265-151-9

Xn, Xi, F, N; R 11-38-51/53-65-67

(Contd. on page 2)

# Safety Data Sheet



according to 1907/2006/EC, Article 31

Printing date 26.01.2009

Revision: 26.01.2009

**Trade name: teslanol Lectro Clean "SP" 400 ml / 200 ml**

(Contd. of page 1)

|   |   |        |
|---|---|--------|
| CAS: 74-98-6<br>EINECS: 200-827-9   | propane<br> F+; R 12         | 25-50% |
| CAS: 109-87-5<br>EINECS: 203-714-2  | dimethoxymethane<br> F; R 11 | 25-50% |
| · <b>Regulation (EC) No 648/2004 on detergents / Labelling for contents</b> |   |        |
| aliphatic hydrocarbons  |   | ≥ 30%  |

· **Additional information:** For the wording of the listed risk phrases refer to section 16.

## 4 First aid measures

· **General information:**

Take affected persons out into the fresh air.  
Do not leave affected persons unattended.  
Immediately remove any clothing soiled by the product.

· **After inhalation:**

Supply fresh air; consult doctor in case of complaints.  
In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

· **After eye contact:** Rinse opened eye for several minutes under running water.

· **After swallowing:**

Do not induce vomiting; call for medical help immediately.  
Show this MSDS

## 5 Fire-fighting measures

· **Suitable extinguishing agents:**

CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· **For safety reasons unsuitable extinguishing agents:** Water with full jet

· **Special hazards caused by the substance, its products of combustion or resulting gases:**

Risk of bursting in case of fire heat

· **Protective equipment:** Do not inhale explosion gases or combustion gases.

· **Additional information** Cool endangered receptacles with water spray.

## 6 Accidental release measures

· **Person-related safety precautions:**

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources.

· **Measures for environmental protection:** Do not allow to enter sewers/ surface or ground water.

· **Measures for cleaning/collecting:**

Ensure adequate ventilation.

Allow to evaporate.

## 7 Handling and storage

· **Handling:**

· **Information for safe handling:**

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

· **Information about fire - and explosion protection:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

(Contd. on page 3)

# Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 26.01.2009

Revision: 26.01.2009

**Trade name: teslanol Lectro Clean "SP" 400 ml / 200 ml**

(Contd. of page 2)

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.  
Do not spray onto a naked flame or any incandescent material.

- **Storage:**
- **Requirements to be met by storerooms and receptacles:**  
Store in a cool location.  
Observe official regulations on storing packagings with pressurized containers.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**  
Store in cool, dry conditions in well sealed receptacles.  
Protect from heat and direct sunlight.
- **Recommended storage temperature:** 15 - 35°C, max. 50°C

## 8 Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

- **Ingredients with limit values that require monitoring at the workplace:**

**64742-49-0 Naphtha (petroleum), hydrotreated light**

TWA (8H) Long-term value: 1000 mg/m<sup>3</sup>, 250 ppm

**109-87-5 dimethoxymethane**

WEL Short-term value: 3950 mg/m<sup>3</sup>, 1250 ppm  
Long-term value: 3160 mg/m<sup>3</sup>, 1000 ppm

- **Additional information:** The lists valid during the making were used as basis.
- **Personal protective equipment:**
- **General protective and hygienic measures:**  
Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing  
Wash hands before breaks and at the end of work.  
Do not inhale gases / fumes / aerosols.  
Avoid contact with the eyes and skin.
- **Respiratory protection:** Use suitable respiratory protective device in case of insufficient ventilation.
- **Protection of hands:**
- **Material of gloves** If contamination is possible, use gloves made of nitrile according EN 374
- **Penetration time of glove material** > 480 min / 0,4 mm thickness
- **Eye protection:** Safety glasses in case of spittings

## 9 Physical and chemical properties

- **General Information**

**Form:** Aerosol  
**Colour:** Colourless  
**Odour:** Ether-like

- **Change in condition**

**Melting point/Melting range:** Undetermined.  
**Boiling point/Boiling range:** -44°C

- **Flash point:** Not applicable, as aerosol.

- **Ignition temperature:** 235°C

- **Self-igniting:** Product is not selfigniting.

- **Danger of explosion:** Risk of bursting at temperatures > 50°C. Damage of the container may lead to the formation of explosive mixtures of gas/vapors with air.

(Contd. on page 4)

# Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 26.01.2009

Revision: 26.01.2009

Trade name: teslanol Lectro Clean "SP" 400 ml / 200 ml

(Contd. of page 3)

- |   |             |
|---|-------------|
| <b>· Explosion limits:</b>  |             |
| <b>Lower:</b>   | 0.8 Vol %   |
| <b>Upper:</b>   | 10.9 Vol %  |
| <b>Pressure (20°C)</b>  | 3 - 5,5 bar |
| <b>· Density at 20°C:</b> 0.65 g/cm <sup>3</sup>                  |             |
| <b>· Solubility in / Miscibility with water:</b> Partly miscible. |             |
| <b>· Solvent content:</b>   |             |
| <b>Organic solvents:</b>  | 71.5 %      |
| <b>· Additional information</b> Vapors are heavier than air.      |             |

## 10 Stability and reactivity

- **Thermal decomposition / conditions to be avoided:** Risk of bursting at temperatures >50°C.
- **Dangerous reactions** By use or incidental release the formation of explosive vapor/air mixtures is possible.
- **Dangerous decomposition products:** In case of fire the formation of toxic gases is possible.
- **Additional information:** Stable for a storage time of min. 24 months

## 11 Toxicological information

- **Acute toxicity:**

- **LD/LC50 values relevant for classification:**

**64742-49-0 Naphtha (petroleum), hydrotreated light**

|            |          |                       |
|------------|----------|-----------------------|
| Oral       | LD50     | > 5000 mg/kg (rat)    |
| Dermal     | LD50     | > 2000 mg/kg (rabbit) |
| Inhalative | LC50/4 h | > 20 mg/l (rat)       |

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** low
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**  
The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:  
Irritant

## 12 Ecological information

- **Ecotoxicological effects:**

- **Aquatic toxicity:**

**64742-49-0 Naphtha (petroleum), hydrotreated light**

|              |                                       |
|--------------|---------------------------------------|
| LC 50 / 96 h | 2.5 mg / l (Flathead Minnow /Elritze) |
|--------------|---------------------------------------|

- **Remark:** Toxic for fish
- **General notes:**  
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water  
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.  
Also poisonous for fish and plankton in water bodies.

(Contd. on page 5)

# Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 26.01.2009

Revision: 26.01.2009

Trade name: teslanol Lectro Clean "SP" 400 ml / 200 ml

Toxic for aquatic organisms

(Contd. of page 4)

## 13 Disposal considerations

- **Product:**
- **Recommendation**  
empty cans: material recycling  
filled cans: remove in accordance with local regulations
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

## 14 Transport information

### · Land transport ADR/RID (cross-border)



- **ADR/RID class:** 2 5F Gases.
- **Danger code (Kemler):** -
- **UN-Number:** 1950
- **Packaging group:** -
- **Hazard label:** 2.1
- **Description of goods:** 1950 AEROSOLS
- **Remarks:** Transportation as "LIMITED QUANTITIES" (LQ2) according 3.4 ADR possible.  
Sole marking: UN 1950 (rhombe)  
Entry in the transportation document: Transportation according chapter 3.4 ADR

### · Maritime transport IMDG:



- **IMDG Class:** 2.1
- **UN Number:** 1950
- **Label** 2.1
- **Packaging group:** -
- **EMS Number:** F-D,S-U
- **Marine pollutant:** No
- **Proper shipping name:** AEROSOLS

### · Air transport ICAO-TI and IATA-DGR:



- **ICAO/IATA Class:** 2.1
- **UN/ID Number:** 1950
- **Label** 2.1
- **Packaging group:** -
- **Proper shipping name:** AEROSOLS, flammable

GB

(Contd. on page 6)

# Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 26.01.2009

Revision: 26.01.2009

Trade name: teslanol Lectro Clean "SP" 400 ml / 200 ml

(Contd. of page 5)

## 15 Regulatory information

· **Labelling according to EU guidelines:**

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

· **Code letter and hazard designation of product:**

*Xi* Irritant  
*F+* Extremely flammable  
*N* Dangerous for the environment

· **Risk phrases:**

12 Extremely flammable.  
 38 Irritating to skin.  
 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
 67 Vapours may cause drowsiness and dizziness.

· **Safety phrases:**

23 Do not breathe aerosol.  
 24/25 Avoid contact with skin and eyes.  
 29/56 Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.  
 51 Use only in well-ventilated areas.

· **Special labelling of certain preparations:**

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.  
 Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking.  
 Without sufficient ventilation formation of explosive mixtures may be possible.  
 Keep out of the reach of children

· **National regulations:**

· **Information about limitation of use:**

Employment restrictions concerning juveniles must be observed.  
 Employment restrictions concerning pregnant and lactating women must be observed.

| Class | Share in % |
|-------|------------|
| NK    | 50-100     |

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant R-phrases**

11 Highly flammable.  
 12 Extremely flammable.  
 38 Irritating to skin.  
 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
 65 Harmful: may cause lung damage if swallowed.  
 67 Vapours may cause drowsiness and dizziness.