

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 07.09.2009

Revision: 07.09.2009

1 Identification of the substance/preparation and of the company/undertaking

- **Product details**
- **Trade name:** *teslanol GR - Gummi Reiniger (Art. 26041)*
- **Application of the substance / the preparation** *Solvent Cleaner*
- **Manufacturer/Supplier:**
*wentronic - Electronic Components Handels GmbH
 Pillmannstrasse 12
 D-38112 Braunschweig
 Deutschland / Germany
 Telefon +49-(0)531-210 58-0
 Telefax +49-(0)531-210 58-22
 office@wentronic.com*
- **Further information obtainable from:**
*Vertrieb / Sales Department (über Zentrale / via switchboard)
 Telefon +49-(0)531-210 58-0
 Telefax +49-(0)531-210 58-22
 office@wentronic.com*
- **Information in case of emergency:**
*Telefon +49-(0)531-210 58-0
 Telefax +49-(0)531-210 58-22
 office@wentronic.com*

2 Hazards identification

- **Hazard description:**



F+ Extremely flammable

- **Information concerning particular hazards for human and environment:**
*The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.
 At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.
 Warning! Pressurized container.
 Has a narcotizing effect.
 R 12 Extremely flammable.
 R 52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
 R 66 Repeated exposure may cause skin dryness or cracking.
 R 67 Vapours may cause drowsiness and dizziness.
 Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.
 Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking.
 Without sufficient ventilation formation of explosive mixtures may be possible.
 Keep out of the reach of children*
- **Classification system:**
The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

3 Composition/information on ingredients

- **Chemical characterization**
- **Description:** *Mixture of substances listed below with nonhazardous additions.*

(Contd. on page 2)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 07.09.2009

Revision: 07.09.2009

Trade name: teslanol GR - Gummi Reiniger (Art. 26041)

(Contd. of page 1)

· Dangerous components:		
CAS: 106-97-8 EINECS: 203-448-7	butane F+; R 12	25-50%
CAS: 64742-48-9 EINECS: 265-150-3	Naphtha (petroleum), hydrotreated heavy Xn; R 10-65-66-67	10-25%
CAS: 67-63-0 EINECS: 200-661-7	propan-2-ol Xi, F; R 11-36-67	10-25%
CAS: 64742-49-0 EINECS: 265-151-9	Naphtha (petroleum), hydrotreated light Xn, Xi, F, N; R 11-38-51/53-65-67	10- <20%
CAS: 74-98-6 EINECS: 200-827-9	propane F+; R 12	2.5-10%
CAS: 75-28-5 EINECS: 200-857-2	isobutane F+; R 12	≤ 2.5%
· Regulation (EC) No 648/2004 on detergents / Labelling for contents		
aliphatic hydrocarbons		≥ 30%

· **Additional information:** For the wording of the listed risk phrases refer to section 16.

4 First aid measures

· **General information:**

Take affected persons out into the fresh air.

Do not leave affected persons unattended.

· **After inhalation:** Supply fresh air; consult doctor in case of complaints.

· **After skin contact:** Wash with water and soap

· **After eye contact:** Rinse opened eye for several minutes under running water.

· **After swallowing:**

If product is swallowed DO NOT induce vomiting. DANGER OF ASPIRATION. Search for medical help and show this MSDS.

5 Fire-fighting measures

· **Suitable extinguishing agents:**

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· **For safety reasons unsuitable extinguishing agents:** Water with full jet

· **Special hazards caused by the substance, its products of combustion or resulting gases:**

Risk of bursting in case of fire heat

· **Protective equipment:** Do not inhale explosion gases or combustion gases.

· **Additional information** Cool endangered receptacles with water spray.

6 Accidental release measures

· **Person-related safety precautions:**

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Avoid contact with skin / eyes and inhalation.

Keep away from ignition sources.

· **Measures for environmental protection:** Do not allow to enter sewers/ surface or ground water.

· **Measures for cleaning/collecting:**

Ensure adequate ventilation.

Let volatiles evaporate - stem up residues mechanically

GB

(Contd. on page 3)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 07.09.2009

Revision: 07.09.2009

Trade name: teslanol GR - Gummi Reiniger (Art. 26041)

(Contd. of page 2)

7 Handling and storage

- **Handling:**
- **Information for safe handling:**
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.
Do not spray onto a naked flame or any incandescent material.
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Store in a cool location.
Observe official regulations on storing packagings with pressurized containers.
- **Information about storage in one common storage facility:** Store away from oxidizing agents.
- **Further information about storage conditions:**
Store in cool, dry conditions in well sealed receptacles.
Protect from heat and direct sunlight.
- **Recommended storage temperature:** 15 - 35°C, max. 50°C

8 Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

- **Ingredients with limit values that require monitoring at the workplace:**

106-97-8 butane

WEL	Short-term value: 1810 mg/m ³ , 750 ppm Long-term value: 1450 mg/m ³ , 600 ppm Carc (if more than 0.1% of buta-1.3-diene)
-----	---

67-63-0 propan-2-ol

WEL	Short-term value: 1250 mg/m ³ , 500 ppm Long-term value: 999 mg/m ³ , 400 ppm
-----	--

- **Additional information:** The lists valid during the making were used as basis.

- **Personal protective equipment:**
- **General protective and hygienic measures:**
Wash hands before breaks and at the end of work.
Do not inhale gases / fumes / aerosols.
Avoid close or long term contact with the skin.

- **Respiratory protection:**
Not necessary if room is well-ventilated.
Use suitable respiratory protective device in case of insufficient ventilation.

- **Protection of hands:**



Protective gloves

- **Material of gloves** If contamination is possible, use gloves made of nitrile according EN 374
- **Penetration time of glove material** > 480 min / 0,4 mm thickness
- **Eye protection:** Safety glasses in case of spittings

GB

(Contd. on page 4)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 07.09.2009

Revision: 07.09.2009

Trade name: teslanol GR - Gummi Reiniger (Art. 26041)

(Contd. of page 3)

9 Physical and chemical properties

· General Information

Form: Aerosol
Colour: Colourless
Odour: Solvent-like

· Change in condition

Melting point/Melting range: Undetermined.
Boiling point/Boiling range: Not applicable, as aerosol.

· **Flash point:** Not applicable, as aerosol.

· **Ignition temperature:** 240°C

· **Self-igniting:** Product is not selfigniting.

· **Danger of explosion:** Risk of bursting at temperatures > 50°C. Damage of the container may lead to the formation of explosive mixtures of gas/vapors with air.

· Explosion limits:

Lower: 0.6 Vol %
Upper: 12.0 Vol %
Pressure (20°C) 2,0 - 4,5 bar

· **Density at 20°C:** 0.65 g/cm³

· Solubility in / Miscibility with water:

Not miscible or difficult to mix.

· Solvent content:

Organic solvents: 56.9 %

· **Additional information** Vapors are heavier than air.

10 Stability and reactivity

- **Thermal decomposition / conditions to be avoided:** Risk of bursting at temperatures >50°C.
- **Dangerous reactions** By use or incidental release the formation of explosive vapor/air mixtures is possible.
- **Dangerous decomposition products:** No dangerous decomposition products known.
- **Additional information:** Stable for a storage time of min. 24 months

11 Toxicological information

· Acute toxicity:

· LD/LC50 values relevant for classification:

64742-48-9 Naphtha (petroleum), hydrotreated heavy

Oral	LD50	>2000 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rab)
Inhalative	LC50/4 h	>5 mg/l (rat)

64742-49-0 Naphtha (petroleum), hydrotreated light

Oral	LD50	>2000 mg/kg (rat)
Dermal	LD50	> 2000 mg/kg (rabbit)
Inhalative	LC50/4 h	> 20 mg/l (rat)

· Primary irritant effect:

- **on the skin:** low irritant - no duty to declare
- **on the eye:** low

(Contd. on page 5)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 07.09.2009

Revision: 07.09.2009

Trade name: teslanol GR - Gummi Reiniger (Art. 26041)

(Contd. of page 4)

· **Sensitization:** No sensitizing effects known.

12 Ecological information

· **Ecotoxicological effects:**· **Acquatic toxicity:**

64742-48-9 Naphtha (petroleum), hydrotreated heavy

LC 50 / 96 h >100 mg / l (fis)

64742-49-0 Naphtha (petroleum), hydrotreated light

LC 50 / 96 h < 10 mg / l (daphnia)

· **Remark:** Harmful to fish· **General notes:**

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Harmful to aquatic organisms

Do not allow product to reach ground water, water course or sewage system.

13 Disposal considerations

· **Product:**· **Recommendation**

empty cans: material recycling

filled cans: remove in accordance with local regulations

· **European waste catalogue**

16 00 00 WASTES NOT OTHERWISE SPECIFIED IN THE LIST

16 05 00 gases in pressure containers and discarded chemicals

16 05 04 gases in pressure containers (including halons) containing dangerous substances

· **Uncleaned packaging:**· **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· **Land transport ADR/RID (cross-border)**· **ADR/RID class:** 2 5F Gases.· **Danger code (Kemler):** -· **UN-Number:** 1950· **Packaging group:** -· **Hazard label:** 2.1· **Description of goods:** 1950 AEROSOLS· **Limited quantities (LQ)** LQ2· **Transport category** 2· **Tunnel restriction code** D

(Contd. on page 6)

GB

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 07.09.2009

Revision: 07.09.2009

Trade name: teslanol GR - Gummi Reiniger (Art. 26041)

(Contd. of page 5)

· **Remarks:** Transportation as "LIMITED QUANTITIES" (LQ2) according 3.4 ADR possible.
Sole marking: UN 1950 (rhombe)
Entry in the transportation document: Transportation according chapter 3.4 ADR

· Maritime transport IMDG:



· **IMDG Class:** 2.1
· **UN Number:** 1950
· **Label** 2.1
· **Packaging group:** -
· **EMS Number:** F-D,S-U
· **Marine pollutant:** No
· **Proper shipping name:** AEROSOLS

· Air transport ICAO-TI and IATA-DGR:



· **ICAO/IATA Class:** 2.1
· **UN/ID Number:** 1950
· **Label** 2.1
· **Packaging group:** -
· **Proper shipping name:** AEROSOLS, flammable

15 Regulatory information

· Labelling according to EU guidelines:

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

· Code letter and hazard designation of product:



F+ Extremely flammable

· Risk phrases:

12 Extremely flammable.
52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
66 Repeated exposure may cause skin dryness or cracking.
67 Vapours may cause drowsiness and dizziness.

· Safety phrases:

23 Do not breathe aerosol.
24/25 Avoid contact with skin and eyes.
29/56 Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.
51 Use only in well-ventilated areas.

· Special labelling of certain preparations:

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.
Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking.

(Contd. on page 7)

Safety Data Sheet
according to 1907/2006/EC, Article 31

Printing date 07.09.2009

Revision: 07.09.2009

Trade name: teslanol GR - Gummi Reiniger (Art. 26041)

(Contd. of page 6)

Without sufficient ventilation formation of explosive mixtures may be possible.
Keep out of the reach of children

· **National regulations:**

· **Information about limitation of use:**

Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be observed.

Class	Share in %
NK	50-100

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant R-phrases**

10 Flammable.

11 Highly flammable.

12 Extremely flammable.

36 Irritating to eyes.

38 Irritating to skin.

51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

65 Harmful: may cause lung damage if swallowed.

66 Repeated exposure may cause skin dryness or cracking.

67 Vapours may cause drowsiness and dizziness.

-GB-